

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



529328

(43) International Publication Date
15 April 2004 (15.04.2004)


PCT

(10) International Publication Number
WO 2004/031586 A1

- (51) International Patent Classification⁷: **F04D 13/02**, 29/00
- (21) International Application Number:
PCT/AU2003/001294
- (22) International Filing Date: 2 October 2003 (02.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2002951793 2 October 2002 (02.10.2002) AU
- (71) Applicant (for all designated States except US): **BRITTON MARINE (AUSTRALIA) PTY. LTD.** [AU/AU]; 15/2-4 Atkinson Rd., Tarren Point, New South Wales 2229 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **BRITTON, Stephen** [AU/AU]; 15/2-4 Atkinson Rd., Tarren Point, New South Wales 2229 (AU).
- (74) Agent: **MOLINS, Michael**; Level 25, Chifley Tower, 2 Chifley Square, Sydney, New South Wales 2000 (AU).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Declaration under Rule 4.17:**
— of inventorship (Rule 4.17(iv)) for US only
- Published:**
— with international search report

[Continued on next page]

(54) Title: **ENGINE COUPLED PUMP WITH 90 DEGREE GEARBOX**



(57) Abstract: A light, powerful and manoeuvrable centrifugal pump unit suitable for fighting fires, emptying flooded compartments and providing auxiliary cooling water on board ships includes a frame (10) which supports a mounting plate (12) through vibration isolating mounts (13). A marine grade water-cooled diesel engine (11) mounted above the plate (12) so that the axis of rotation is vertical. A 90 degree gear box (16) driven by the engine (11) is mounted below the plate (12) and drives the pump (17) of which the axis of rotation is horizontal. Also suitable for fighting fires in rural and remote environments.

WO 2004/031586 A1